

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023 Revision date 29-Jun-2023 Revision Number 1.04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1	.1	Pr	od	uct	identifier

Product Name BOSTIK 6330 GLUE STICKS 300 MM

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Hot-melt adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children

BOSTIK 6330 GLUE STICKS 300 MM

Revision date 29-Jun-2023 Revision Number 1.04

Supercedes Date: 29-Jun-2023

2.3. Other hazards

Contact with product at elevated temperatures can result in thermal burns.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Vinyl acetate	(607-023-00- 0) 203-545-4	108-05-4	0.1 - <0.3	Flam Liq. 2 (H225) Acute Tox. 4 (H332) Carc. 2 (H351) STOT SE 3 (H335) STOT SE 3 (H336) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	-	01-2119471301- 50-XXXX

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Vinyl acetate - 108-05-4	D

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice

If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.

Inhalation

	Molten . Move to fresh air in case of accidental inhalation of vapours or decomposition products. Solid: . Not an expected route of exposure.
Eye contact	Solid: In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Molten . Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Contact with molten materials requires immediate medical assistance.
Skin contact	Solid: Wash skin with soap and water. Molten After contact with molten product, cool skin area rapidly with cold water. For severe burns, immediate medical attention is required. Do not remove clothing if adhering to skin. Removal of solidified molten material from skin requires medical assistance. Do not try to removed solidified material from the skin.
Ingestion	Get immediate medical attention. Do not induce vomiting without medical advice.
4.2. Most important symptoms and	d effects, both acute and delayed
Symptoms	Contact with molten substance may cause severe burns to skin and eyes.
4.3. Indication of any immediate m	edical attention and special treatment needed
Note to doctors	Burns caused by molten material must be treated clinically. Treat any burns as thermal burns, after decontamination.
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	CO2, dry chemical, dry sand, alcohol-resistant foam.
Suitable Extinguishing Media Unsuitable extinguishing media	CO2, dry chemical, dry sand, alcohol-resistant foam. Do not use straight streams.
	Do not use straight streams.
Unsuitable extinguishing media	Do not use straight streams.
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the	Do not use straight streams. <u>he substance or mixture</u> The product is insoluble and floats on water. The melted product can cause severe
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical	Do not use straight streams. <u>he substance or mixture</u> The product is insoluble and floats on water. The melted product can cause severe burns.
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters	Do not use straight streams. <u>he substance or mixture</u> The product is insoluble and floats on water. The melted product can cause severe burns.
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. ase measures
Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releat 6.1. Personal precautions, protect	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. ase measures ive equipment and emergency procedures
Unsuitable extinguishing media 5.2. Special hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releat 6.1. Personal precautions, protect Personal precautions	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. ase measures ive equipment and emergency procedures Ensure adequate ventilation. Avoid contact with hot, molten product.
Unsuitable extinguishing media 5.2. Special hazards arising from the chemical Hazardous combustion products 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental relevent 6.1. Personal precautions, protect Personal precautions Other information	Do not use straight streams. he substance or mixture The product is insoluble and floats on water. The melted product can cause severe burns. Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment. ase measures ive equipment and emergency procedures Ensure adequate ventilation. Avoid contact with hot, molten product. Where possible allow molten material to solidify naturally.

6.3. Methods and material for containment and cleaning up

Molten . Cover with dry sand/earth.		
Solid: . Take up mechanically, placing in appropriate containers for disposal. Molten . Where possible allow molten material to solidify naturally. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust. Clean contaminated surface thoroughly.		
Clean contaminated objects and areas thoroughly observing environmental regulations.		
See section 8 for more information. See section 13 for more information.		
orage		
_		
Avoid contact with skin and eyes. Wash thoroughly after handling. Take precautionary measures against static discharges. Use adequate ventilation and/or engineering controls in high temperature processing to prevent exposure to vapours. Facilities for quickly drenching the body should be provided within the immediate work area for emergency use where there is a possibility of exposure.		
Handle in accordance with good industrial hygiene and safety practice.		
cluding any incompatibilities		
Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.		
Keep at temperatures between 10 and 35 °C.		
The information required is contained in this Safety Data Sheet.		
Observe technical data sheet.		

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Vinyl acetate	TWA: 5 ppm	TWA: 5 ppm
108-05-4	TWA: 17.6 mg/m ³	TWA: 17.6 mg/m ³
	STEL: 10 ppm	STEL: 10 ppm
	STEL: 35.2 mg/m ³	STEL: 35.2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Vinyl acetate (108-05-4)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker	Inhalation	17.6 mg/m ³			

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023

Long term Systemic health effects			
worker Short term Systemic health effects	Inhalation	35.2 mg/m³	
worker Long term Local health effects	Inhalation	17.6 mg/m³	
worker Short term Local health effects	Inhalation	35.2 mg/m³	
worker Long term Systemic health effects	Dermal	0.42 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
Vinyl acetate (108-05-4)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.016 mg/l			
Marine water	0.002 mg/l			
Microorganisms in sewage treatment	6 mg/l			
Freshwater sediment	0.067 mg/kg dry weight			
Marine sediment	0.007 mg/kg dry weight			
Soil	0.004 mg/kg dry weight			

8.2. Exposure controls

Engineering controls

Molten . Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment Eye/face protection	Wear safety glasses with side shields (or goggles). Eyewash fountains should be provided in areas where there is any possibility that workers could be exposed to the substances; this is irrespective of the recommendation involving the wearing of eye protection.
Hand protection	Molten . Heat resistant gloves are recommended when handling molten materials. Solid: . For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves must conform to standard EN 374
Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties						
Physical state	Solid					
Colour	White					
Odour	No information available.					
Odour threshold	No information available					
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>				
Property Melting point / freezing point	<u>Values</u> 80 °C	Remarks • Method				
		Remarks • Method				
Melting point / freezing point	80 °C					
Melting point / freezing point Initial boiling point and boiling	80 °C					

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023 Revision date 29-Jun-2023 Revision Number 1.04

Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH .		Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	100	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Sta	bility and reactivity
-----------------	-----------------------

|--|

Reactivity	No information available.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
10.3. Possibility of hazardous read	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Extremes of temperature and direct sunlight. To avoid thermal decomposition, do not overheat. Do not add water or other volatile material to molten adhesive. Under dusty conditions avoid all sources of ignition, including sparks and static electricity.
10.5. Incompatible materials	

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023

Incompatible materials	Strong oxidising agents, strong acids, and strong bases.	
10.6. Hazardous decomposition pro	oducts	
Hazardous decomposition products	Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.	
SECTION 11: Toxicological i	nformation	
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008	
Information on likely routes of exp	osure	
Product Information		
Inhalation	Based on available data, the classification criteria are not met.	
Eye contact	Based on available data, the classification criteria are not met.	
Skin contact	Based on available data, the classification criteria are not met.	
Ingestion	Based on available data, the classification criteria are not met.	
Symptoms related to the physical,	chemical and toxicological characteristics	
Symptoms	No information available.	
Acute toxicity		
Numerical measures of toxicity		
The following values are calculated ATEmix (oral)	d based on chapter 3.1 of the GHS document >5000 mg/kg	

	20000 mg/ng
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Vinyl acetate	=2900 mg/kg (Rattus)	= 2335 mg/kg (Oryctolagus cuniculus)	=11.4 mg/L (Rattus) 4 h = 3680 ppm (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Vinyl acetate (108-05-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Vinyl acetate (108-05-4)

United Kingdom - BE

BOSTIK 6330 GLUE STICKS 300 MM

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Vinyl acetate (108-05-4)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		No sensitisation responses
Sensitisation: Local Lymph Node			were observed
Assay			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information Vinyl acetate (108-05-4)

Method	Species	Results
OECD Test No. 473: In vitro Mammalian	Human lymphocytes, in vitro	Mutagenic
Chromosome Aberration Test		
OECD Test No. 471: Bacterial Reverse		Not mutagenic in AMES Test
Mutation Test		-

Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information

Method	Species	Results
	Rat	Carcinogenic
Toxicity/Carcinogenicity Studies		

Chemical name	European Union
Vinyl acetate	Carc. 2

Reproductive toxicity

Based on available data, the classification criteria are not met.

Vinyl acetate (108-05-4)

Method	Species	Results
OECD Test No. 416: Two-Generation	Rat	NOAEL 100 mg/kg bw/d
Reproduction Toxicity		

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Vinyl acetate (108-05-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408:	Mouse, female	Oral		91 days	NOAEL: 281 mg/kg
Repeated Dose 90-Day					
Oral Toxicity Study in					

BOSTIK 6330 GLUE STICKS 300 MM

Supercedes Date: 29-Jun-2023

Rodents				
OECD Test No. 408:	Mouse, male	Oral	91 days	NOAEL 285 mg/kg
Repeated Dose 90-Day				
Oral Toxicity Study in				
Rodents				
OECD Test No. 408:	Rat, male	Oral	91 days	NOAEL 684 mg/kg
Repeated Dose 90-Day				
Oral Toxicity Study in				
Rodents				
OECD Test No. 408:	Rat, female	Oral	91 days	NOAEL 810 mg/kg
Repeated Dose 90-Day				
Oral Toxicity Study in				
Rodents				

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Vinyl acetate 108-05-4	-	LC50 96 h = 14 mg/L (Pimephales promelas static)	mg/L 5 min	EC50 48 h = 12.6 mg/L (Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Vinyl acetate (108-05-4)

Method	Exposure time	Value	Results
OECD Test No. 301C: Ready	14 days	82-92% biodegradation	Readily biodegradable
Biodegradability: Modified MITI Test			
(I) (TG 301 C)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Vinyl acetate	0.73

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Vinyl acetate	The substance is not PBT / vPvB PBT assessment does
	not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

Lana				
14.1	UN number or ID number	Not regulated		
14.2	UN proper shipping name	Not regulated		
14.3	Transport hazard class(es)	Not regulated		
14.4	Packing group	Not regulated		
14.5	Environmental hazards	Not applicable		
14.6	Special precautions for user			
S	pecial Provisions	None		
IMDG	<u> </u>			
14.1	UN number or ID number	Not regulated		
14.2	UN proper shipping name	Not regulated		
14.3	Transport hazard class(es)	Not regulated		
14.4	Packing group	Not regulated		
14.5	Marine pollutant	NP		
14.6	Special precautions for user			
S	pecial Provisions	None		
14.7	Maritime transport in bulk			
accor	according to IMO instruments			
Т	ransport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable		

<u>Air transport (ICAO-TI / IATA-DGR)</u>

14.1	UN number or ID number	Not regulated
110	UN proper chipping name	Not regulated

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023

Revision date 29-Jun-2023 Revision Number 1.04

- 14.3 Transport hazard class(es) Not regulated Not regulated
- 14.4 Packing group
- Not applicable 14.5 Environmental hazards
- 14.6 Special precautions for user **Special Provisions** None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note D: Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on

BOSTIK 6330 GLUE STICKS 300 MM Supercedes Date: 29-Jun-2023 Revision date 29-Jun-2023 Revision Number 1.04

the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised' Legend TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit) Ceiling Limit Value Ceiling Skin designation SVHC Substance(s) of Very High Concern Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals Specific target organ toxicity - Repeated exposure Specific target organ toxicity - Single exposure STOT RE STOT SE European Waste Catalogue EWC ADR European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG International Maritime Dangerous Goods (IMDG) ΙΑΤΑ International Air Transport Association (IATA) RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and source No information available Prepared By Revision date Indication of changes	ces for data Product Safety & Regulatory Affairs 29-Jun-2023
Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet