

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: STICK 2 HARD PLASTIC ADHESIVE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND

Tel: 0044 113 240 3456

Fax: 0044 113 240 0024

Email: sds@everbuild.co.uk

1.4. Emergency telephone number

Emergency tel: 0044 113 240 3456 (office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F: R11; Xi: R36/37; Xn: R40; -: R66; -: R67

Classification under CLP: Eye Irrit. 2: H319; STOT SE 3: H336; Carc. 2: H351; Flam. Liq. 1: H224; STOT SE 3: H335

Most important adverse effects: Highly flammable. Irritating to eyes and respiratory system. Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H224: Extremely flammable liquid and vapour.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

Signal words: Danger

Hazard pictograms: GHS02: Flame

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 2

GHS07: Exclamation mark

GHS08: Health hazard



Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+313: IF exposed or concerned: Get medical advice/attention.
P370+378: In case of fire: Use carbon dioxide, foam or dry powder for extinction.
P261: Avoid breathing vapours.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P281: Use personal protective equipment as required.
P312: Call a POISON CENTER or doctor if you feel unwell.
P337+313: If eye irritation persists: Get medical attention.
P403+233: Store in a well-ventilated place. Keep container tightly closed.
P405: Store locked up.
P501: Dispose of contents to hazardous waste.

Label elements under CHIP:

Hazard symbols: Highly flammable.

Harmful.



Risk phrases: R11: Highly flammable.

R36/37: Irritating to eyes and respiratory system.

R40: Limited evidence of a carcinogenic effect.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S36/37: Wear suitable protective clothing and gloves.

S46: If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 3

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%

TETRAHYDROFURAN

203-726-8	109-99-9	F: R11; -: R19; Xi: R36/37; Xn: R40	Flam. Liq. 2: H225; Eye Irrit. 2: H319; Carc. 2: H351; STOT SE 3: H335; -: EUH019	30-50%
-----------	----------	-------------------------------------	---	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 4

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel. If outside keep bystanders upwind and away from danger point. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties. Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	100ppm	125ppm	-	-

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

TETRAHYDROFURAN

UK	150 mg/m3	300 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Protective gloves. Change gloves regularly to prevent permeability.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Fast

Oxidising: No data available.

Solubility in water: Miscible

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Flash point°C: <21

Autoflammability°C: >200

Relative density: ~0.8

pH: n/a

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

TETRAHYDROFURAN

IPR	MUS	LD50	1900	mg/kg
IPR	RAT	LD50	2900	mg/kg
ORL	RAT	LD50	1650	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 7

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

ACETONE

BLUEGILL (<i>Lepomis macrochirus</i>)	LC50	8300	mg/l
---	------	------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of according to local or national legislation Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Completely emptied packaging or practically empty packaging containing dried/cured residues can be disposed of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 8

(ACETONE; TETRAHYDROFURAN)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: I

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 1

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH019: May form explosive peroxides.

EUH066: Repeated exposure may cause skin dryness or cracking.

H224: Extremely flammable liquid and vapour.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

R11: Highly flammable.

R19: May form explosive peroxides.

R36/37: Irritating to eyes and respiratory system.

R36: Irritating to eyes.

R40: Limited evidence of a carcinogenic effect.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

[cont...]

SAFETY DATA SHEET
STICK 2 HARD PLASTIC ADHESIVE

Page: 9

Legend to abbreviations: PNEC = predicted no effect level
DNEL = derived no effect level
LD50 = median lethal dose
LC50 = median lethal concentration
EC50 = median effective concentration
IC50 = median inhibitory concentration
dw = dry weight
bw = body weight
cc = closed cup
oc = open cup
MUS = mouse
GPG = guinea pig
RBT = rabbit
HAM = hamster
HMN = human
MAM = mammal
PGN = pigeon
IVN = intravenous
SCU = subcutaneous
SKN = skin
DRM = dermal
OCC = ocular/corneal
PCP = physico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.