



SAFETY DATA SHEET
QUICK DRYING BLACK SATIN

Page 1
Issued: 08/03/06
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: QUICK DRYING BLACK SATIN
Product code: SATBW
Company name: Rustins Ltd
Waterloo Road
Cricklewood
London
NW2 7TX
United Kingdom
Tel: +44 (0)208 450 4666
Fax: +44 (0)208 452 2008
Emergency tel: +44 (0)208 205 8709

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DOW DPNB 1-10%
CAS: 029911-28-2
[Xi] R36/38
• TEXANOL <1%
[-] R52

3. HAZARDS IDENTIFICATION

Main hazards: No significant hazard.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: No symptoms are expected.
Eye contact: May cause irritation.
Ingestion: No specific data. Expected to be non-toxic.
Inhalation: No symptoms are expected.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.
Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.
Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at rest and obtain medical attention.
Inhalation: If effects occur remove to fresh air and seek medical advice.

SAFETY DATA SHEET
QUICK DRYING BLACK SATIN

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide (CO₂). Dry chemical powder. Alcohol resistant foam. Water spray.

Exposure hazards: In a fire, hazardous decomposition products such as smoke and Carbon Monoxide may be produced.

Protection of fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Ventilate the area.

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes contact the relevant environment agency.

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Clean preferably with a detergent, avoid the use of solvents.

7. HANDLING AND STORAGE

Handling requirements: Avoid inhalation of vapour. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use.

Storage conditions: Store in cool, well ventilated area. KEEP AWAY FROM FREEZING, minimum storage temperature 5 degrees C. Keep away from direct sunlight. Keep container tightly closed. Take precautionary measures to prevent product spills into drains, the ground or waters.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: If there is a risk of exposure to high vapour concentrations, use respiratory protective equipment. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Hand protection: Protective gloves.

Eye protection: Eye protection designed to protect against liquid splashes should be worn.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

SAFETY DATA SHEET
QUICK DRYING BLACK SATIN

Colour: Black
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Miscible
Viscosity: Viscous
Flash point°C: >58
Relative density: 1.18-1.22 @ 20 deg C

10. STABILITY AND REACTIVITY

Stability: Stable under normal storage and handling conditions (see Section 7).
Conditions to avoid: Not applicable. For ideal storage conditions see section 7.
Materials to avoid: Oxidising agents. Strong acids.
Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may be produced.

11. TOXICOLOGICAL INFORMATION

Routes of exposure: There is no data available on the product itself.

12. ECOLOGICAL INFORMATION

Mobility: Soluble in water. Partially volatile. Readily absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: There is no data available on the product itself. Not expected to bioaccumulate.
Other adverse effects: There is no data available on the product itself. It is unlikely this material will present an environmental hazard.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID****IMDG / IMO****IATA / ICAO****15. REGULATORY INFORMATION**

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

SAFETY DATA SHEET
QUICK DRYING BLACK SATIN

applicable national, international and local regulations or provisions. Safety Data Sheet complies with UK regulatory references in accordance with CHIP 3.1.

16. OTHER INFORMATION

Risk phrases used in s.2: R36/38: Irritating to eyes and skin.

R52: Harmful to aquatic organisms.

Legal disclaimer: Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.