

LAYOUT INK BLUE FLUID

Page: 1 Compilation date: 05/12/2014 Revision date: 03/02/2016

Revision No: 8

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: LAYOUT INK BLUE FLUID

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metal Marking Ink

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

	ROCOL House
	Swillington
	Leeds
	West Yorkshire
	LS26 8BS
	ENGLAND
Tel:	+44 (0) 113 232 2700
Fax:	+44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 2: H225; -:
	EUH066
Most important adverse effects:	Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and
	vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to
	aquatic life with long lasting effects.

2.2. Label elements

Label elements:		
Hazard statements:	EUH066: Repeated exposure may cause skin dryness or cracking.	
	H225: Highly flammable liquid and vapour.	
	H319: Causes serious eye irritation.	
	H336: May cause drowsiness or dizziness.	
	H412: Harmful to aquatic life with long lasting effects.	
Hazard pictograms:	GHS02: Flame	
	GHS07: Exclamation mark	[cont]

LAYOUT INK BLUE FLUID



Signal words: Danger

Precautionary statements:
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards
Path State State

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE - REACH registered number(s): 01-2119471330-49-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	50-70%

PROPAN-2-OL

200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
BASIC BLUE 26	6			

219-943-6	2580-56-5	-	Acute Tox. 4: H302; Eye Irrit. 2: H319;	<1%	
			Aquatic Chronic 1: H410		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

LAYOUT INK BLUE FLUID

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal prec	autions, protective	e equipment and	emergency	procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

LAYOUT INK BLUE FLUID

ection 7: Hand	ling and storage						
7.1. Precaution	s for safe handling						
Handling re	equirements: Avoid dire	ect contact w	ith the substan	ce. Ensu	re there is sufficie	nt ventilation of	the area.
	Do not handle in a confined space. Avoid the formation or spread of mists in the air.						
Smoking is forbidden. Use non-sparking tools.							
7.2. Conditions	for safe storage, includ	ing any inc	ompatibilities				
Storage	e conditions: Store in a	cool, well ve	entilated area.	Keep cor	ntainer tightly close	d. Keep away fi	rom
-				•	ectrostatic charge i	•	
	Ensure lig	hting and el	ectrical equipm	nent are r	not a source of igni	tion.	
Suitabl	e packaging: Must only	be kept in o	riginal packagi	ng.			
7.3. Specific en	d use(s)						
Specifi	c end use(s): No data a	vailable.					
-	sure controls/persona		n				
8.1. Control par	rameters						
Hazardous in	aredients:						
ACETONE	5						
				Decision	h la slova (
_	posure limits:			-	ble dust		
State	8 hour TWA	15 m	in. STEL	8	hour TWA	15 min.	SIEL
UK	1210 mg/m3		3620 mg/m3		-		-
PROPAN-2-O							
UK	400 ppm, 999 mg/m3	500 ppm,	, 1250 mg/m3		-		-
DNEL/PNEC Va	lues						
Hazardous in	gredients:						
ACETONE							
Туре		Exposure		Value	Popula	tion	Effect
DNEL		Dermal		186	Work	ers	Local
			1			1	

DNEL	Dermal	186	Workers	Local
DNEL	Inhalation	2420	Workers	Local
DNEL	Oral	62	Consumers	Systemic
PNEC	Fresh water	10.6	-	-
PNEC	Marine water	1.06	-	-
PNEC	Soil (agricultural)	33.3	-	-
PNEC	-	-	-	-

LAYOUT INK BLUE FLUID

Engineering measures:Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
equipment are not a source of ignition.Respiratory protection:Self-contained breathing apparatus must be available in case of emergency.Hand protection:Gloves (solvent-resistant). Latex gloves.Eye protection:Safety glasses. Ensure eye bath is to hand.Skin protection:Protective clothing.Environmental:Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

8.2. Exposure controls

9.1. Information on basic physical and chemical properties

State:	Liquid		
Colour:	Blue		
Odour:	Alcoholic		
Evaporation rate:	Fast		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Also soluble in:	Acetone.		
Viscosity:	Non-viscous		
Boiling point/range°C:	56	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	-18 Pa	rt.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	No data available.	pH:	No data available.
VOC g/I:	No data available.		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

LAYOUT INK BLUE FLUID

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3	gm/kg
ORL	RAT	LD50	5800	mg/kg

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

BASIC BLUE 26

ORL RAT LD50 900 mg/kg	
--------------------------------	--

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

LAYOUT INK BLUE FLUID

Page: 7

Section 12: Ecological information					
12.1. Toxicity					
Hazardous ingredients:					
ACETONE		1			
BLUEGILL (Lepomis macro	rochirus) LC50 8300 mg/l				
BASIC BLUE 26					
TROUT		96H LC50	100	mg/l	
12.2. Persistence and degradability					
Persistence and degradability: Biodegradable.					
12.3. Bioaccumulative potential					
· · · ·					
Bioaccumulative potential:	No bloaccumulation poter				
12.4. Mobility in soil					
Mobility:	Readily absorbed into soi	Ι.			
12.5. Results of PBT and vPv	B assessment				
PBT identification:	PBT identification: This product is not identified as a PBT/vPvB substance.				
12.6. Other adverse effects					
Other adverse effects:	Other adverse effects: Negligible ecotoxicity.				
Section 13: Disposal conside	erations				
13.1. Waste treatment metho	ds				
Disposal operations:	Transfer to a suitable con	tainar and arrange for	collection by specia	licod disposal	
Disposal operations.		tainer and arrange for	collection by specia	liseu uisposai	
Recovery operations:	company.				
Waste code number:					
Disposal of packaging:	Dispose of in a regulated	landfill site or other m	ethod for hazardous	or toxic wastes.	
	The user's attention is dra				
	regulations regarding disp	oosal.			
Section 14: Transport inform	nation				
14.1. UN number					
UN number:	LIN1993				

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(contains acetone, propan-2-ol)

LAYOUT INK BLUE FLUID

Marine pollutant: No

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H225: Highly flammable liquid and vapour.
	H302: Harmful if swallowed.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H410: Very toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.