



www.rustins.co.uk

PRODUCT DATA SHEET

Product	Polyurethane Varnish Stain Satin & Gloss					
Type	A high build, air-drying coloured polyurethane. The finish produced is tough, durable and resistant to oil, water and many chemicals.					
Intended Use	Bare wood, Hardboard, MDF, unsealed cork. Interior use only. For floors, use Rustins' Polyurethane Floor Sealer.					
Special Features	Stains and Varnishes in one. High abrasion and mechanical impact resistance. Colours available: Mahogany, Oak, Dark Oak, Pine, Teak, Walnut & Antique pine. In Satin or Gloss.					
Preparation	The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. Remove wax by rubbing with White Spirit and a plastic scouring pad and wipe away whilst still wet. Cracks may be filled with Rustins' Woodstopping.					
Application	Apply evenly, finishing in the direction of the grain using a good quality brush. The first coat may be thinned with White Spirit (1 part to 8 parts varnish), to act as a sealer when applying to absorbent surfaces.					
Coats	2 coats are usually sufficient on wood. Cork and more absorbent surfaces will require extra coats.					
Drying Time	Touch dry in approximately 2-4 hours, depending on the temperature and humidity.					
Re-coating Time	Re-coat when the previous coat is hard dry, typically within 48 hours depending on the temperature and humidity.					
Application Temp.	Ideally 15-25°C. Do not use below 10°C or in conditions of high humidity.					
Coverage	14-16 sq.m per litre, 1 coat, depending on the absorbency of the surface.					
Maintenance	The varnish will take about 24 hours to dry fully. Afterwards, the surface may be kept clean by wiping with a mild detergent solution when necessary. To restore the gloss, a wax polish may be applied. Worn areas may be re-coated once cleaned, dewaxed and lightly sanded to provide a key.					
Compatibility	<p>The varnish may be used over the following Rustins products; Woodstopping, Grainfiller, Rustins Polyurethane Varnish.</p> <p>This material is not a paint and the colour will darken with additional coats. A lighter shade can be obtained by diluting with White Spirit</p> <p>Rustins Polyurethane Clear Varnish may be applied over Varnish Stain without altering the colour.</p> <p>Important: If any other products are used, such as timber treatments, which may contain wax, these must be tested first for compatibility. Old existing coatings may be successfully re-coated with Rustins Polyurethane Varnish once the surface has been thoroughly cleaned, dewaxed and lightly sanded to provide a key.</p>					
Settlement	STIR WELL BEFORE USE. Satin and Matt finishes may dry glossy if not thoroughly stirred.					
Shelf-life/Storage	Many years in normal conditions, if stored in original, tightly closed container.					
Hazards	Flammable. Keep out of reach of children. Keep away from sources of ignition-no smoking. Avoid contact with eyes and skin, Use only in well ventilated areas. A full Health & Safety Data Sheet is available upon request.					
Clean-Up	Use White Spirit or Rustins Brush Cleaner whilst still wet. If dried on, clean equipment and brushes with Rustins Brush Restorer.					
Sizes	250ml	500ml	1 litre	2.5 litre	5 litre	Gloss, Satin and Matt