



SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 1
Compilation date: 21/08/2012
Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: YACHT VARNISH - GLOSS & SATIN

Product code: YACV

Synonyms: YACHT VARNISH

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666

Fax: +44 (0)208 452 2008

Email: rustins@rustins.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; -: R66

Most important adverse effects: Flammable. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements under CHIP:

Risk phrases: R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S23: Do not breathe.

Precautionary phrases: Contains . May produce an allergic reaction.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 2

Hazardous ingredients:

CALCIUM DRIER 4%

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|--------|-----|------------------------------------|--------------------|---------|
| - | - | -: R10; N: R51/53; Xn: R65; -: R66 | - | 1-10% |

NAPHTHA (PETROLEUM) HYDROTREATED HEAVY

| | | | | |
|-----------|------------|-------------------------|---|--------|
| 265-150-3 | 64742-48-9 | Xn: R65; -: R66; -: R67 | - | 30-50% |
|-----------|------------|-------------------------|---|--------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If irritation persists seek medical attention.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at rest and obtain medical attention.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth if unconscious, place in the recovery position and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation with short term redness and stinging.

Ingestion: May cause nausea and diarrhoea.

Inhalation: May cause irritation of the respiratory tract.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO₂). Dry chemical powder. Alcohol resistant foam. Sand or earth. Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In a fire, hazardous decomposition products such as smoke and Carbon Monoxide may be produced.

5.3. Advice for fire-fighters

Advice for fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do NOT allow run-off from fire fighting to enter drains or water courses.

[cont...]

SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 3

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing (see section 8).

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water company should be contacted immediately. In the case of contamination of streams, rivers or lakes contact the relevant environment agency.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite. Transfer into a suitable container for disposal in accordance with the waste regulations (see section 13) Do not use equipment in clean-up procedure which may produce sparks. Clean preferably with a detergent, avoid the use of solvents.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin and eye contact. Smoking, eating and drinking should be prohibited in areas of storage and use. Exclude sources of heat, sparks and open flame. Earth any equipment used in handling. Use non-sparking tools. The Manual Handling Operations Regulations may apply to the handling of containers of this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in containers, should be observed.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

[cont...]

SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 4

8.1. Control parameters

Workplace exposure limits: Not applicable.

8.2. Exposure controls

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see Respiratory protection below).

Respiratory protection: All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Hand protection: Where repeated skin exposure may occur, wear Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale amber.

Odour: Paraffinic.

Solubility in water: Not miscible

Boiling point/range °C: 150-190

Flash point °C: 38

Relative density: 0.905 @ 20C

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

10.5. Incompatible materials

Materials to avoid: Oxidising agents. Strong acids.

[cont...]

SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may be produced.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: Not applicable.

Symptoms / routes of exposure

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation with short term redness and stinging.

Ingestion: May cause nausea and diarrhoea.

Inhalation: May cause irritation of the respiratory tract.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility: Insoluble in water. Partially volatile. Partially absorbed into soil. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: There is no data available on the product itself.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

[cont...]

SAFETY DATA SHEET
YACHT VARNISH - GLOSS & SATIN

Page: 6

14.2. UN proper shipping name

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: The product complies with the requirements of the Toy Safety Regulations, BS EN 71 Part 3 1995. A certificate of conformity can be supplied upon request.

Phrases used in s.2 and 3: R10: Flammable.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.